

CC02-7000

WIRE CUTTER

Warning! This tool should not be used on live electrical circuits. It is not protected against electrical shock! Always use OSHA/ANSI/CE or other industry approved eye protection when using tools. This tool is not to be used for purposes other than intended. Read carefully and understand instructions before using this tool.



Specification

- Length 7" / 180mm
- Blades of high carbon steel induction hardened, cutting edge
- Weight 233g

Capacity

- 5mm Dia Wire rope
- 4mm Dia Steel wire rope
- 2.5mm Dia Piano wire



Applications:

- Breaking into fiber cables containing strength members that would damage conventional wire cutters. Mini-Coax, centre conductors/ stingers of copper coated steel.
- Conventional wire cutting within the tools capacity.
- Electrical, Automotive, Industrial uses.

BENEFITS

- Induction hardened blades provide a clean cut of wire without flattening, fanning and splaying
- Handles padded with soft component for comfort in use
- Ergonomic design makes low hand force and provides a mechanical advantage to achieve an easier cut
- Smaller open width of handles makes it easy to close back and fits any hand comfortably
- Light weight and spring loaded to help reduce hand fatigue

Maintenance

- Keep cutting edges clean from cable debris and gel.
- Lubricate metal parts on a regular basis using a water dispersant lubricant.

WARRANTY: RIPLEY warrants its products against defective materials and workmanship for a period of one year from date of shipment from the RIPLEY factory provided the product is utilized in accordance with instructions and specified ratings.



46 Nooks Hill Road
Cromwell, CT 06416
USA.
Phone: 800-528-8665
Int'l: (01) 860-635-2200
Fax: (01) 860-635-3631
Internet: www.ripley-tools.com

Ripley Europe Ltd
Building 47, Bay 4, Second Avenue,
The Pensnett Estate, Kingswinford
West Midlands, England, DY6 7UZ. UK.
Phone: +44(0)1384400070
Fax: +44(0)1384400060
CSRUK@ripley-tools.com
Web: www.ripley-tools.com



Doc. No. CC02-6000
Approval: 02-27-19