## AJST/T10

## **Armored Jacket Stripping Tool**

*Warning*! This tool should not be used on live electrical circuits. It is not protected against electrical shock! Always use OSHA/ANSI or other industry approved eye protection when using tools. This tool is not to be used for purposed other than intended. Read carefully and understand instructions before using this tool.

The AJST/T10 (Armored Jacket Stripping Tool) is designed to manually remove the outer jacket, steel tape armor, and inner jacket on TFC JBA series solid sheath trunk and distribution coax cable. AJST/T10 Tools are available in the trunk sizes listed below Further cable preparation can be performed with Cablematic CST tool models. Cutting heads are color coded similar to our CST guide sleeves. The use of a hacksaw is recommended to keep the end of the cable as round as possible before using the AJST/T10. Some distortion is allowable as long as the cable is round enough to enter the tool.

## **IMPORTANT NOTICE:**

Approved eye and hand protection must be used during operation of this tool. Serious injury may be caused by the armor curl that exits the tool.

## **OPERATING INSTRUCTIONS**

**Step 1**. (Fig. 1) To remove the outer jacket, armor, and inner jacket, place the blade end of the tool onto the cable. Turn and engage the blade into the jacket.

**Step 2**. Rotate the tool in a clock-wise direction using slight forward pressure. Train the stripped jacket curl with a gloved hand or snip off the curl if it becomes too long. To stop the stripping action, place your hand firmly on the cable and rotate the tool against your hand.



FIG 1

TFC JBA ARMORED CABLE			
CABLE SIZE	TOOL MODEL	TOOL PART NUMBER	COLOR
500/T10	AJST 500/T10**	36243**	RED
625/T10	AJST 625/T10**	36245**	BLUE
750/T10	AJST 750/T10	36247	GREEN
875/T10	AJST 875/T10	36249	GOLD

<sup>\*\*</sup> Special order items. Consult factory on availability.

Replacement blade for all AJST/T10 tools is CB 213.

WARRANTY: RIPLEY warrants its products against defective materials and workmanship for a period of one year from date of shipment from the RIPLEY factory provided the product is utilized in accordance with instructions and specified ratings.



